CO₂ PORTABLE FIRE EXTINGUISHERS

(UL LISTED)

PRODUCT DESCRIPTION



NAFFCO CO_2 gas extinguishers are characterized by their high performance for fires including items at risk for electrical shorts like computer, office equipment and generators etc. CO_2 is non conductive, clean and safe, ensuring minimal damage to electrical equipment and furnishings. Suitable for Class B fire risks.



FEATURES

- Carbon Dioxide is the trusted non-conductive cleaning agent and is most effective for dealing with electronic equipment fires. CO_2 is suitable for use on Class B and Class C fires.
- TYPICAL USES: For protecting sensitive electronic equipment in offices, classrooms, parking garages, and hotel/motel assembly halls and guest areas. For protecting sensitive electronic equipment in businesses such as retail stores, light manufacturing facilities, research facilities, auto dealerships, vehicle/
- aircraft/marine service centers, and manufacturing processes such as painting, dipping, and coating.
- Not suitable for use on fires involving cooking oil and grease. Recommended for use on sensitive electronic equipment.

SPECIFICATION

3F LCII ICATION				
Model Number	N 05LC	N 10LC	N 15LC	N 20LC
Agent Capacity	5 lb. (2.27 kg)	10 lb. (4.54 kg)	15 lb. (6.8 kg)	20 lb. (9.07 kg)
UL Rating	5-B:C	10-B:C	10-B:C	10-B:C
Discharge Time	9 sec	9 sec	15 sec	20 sec
Range (FT/M)	4-8 / 1.2-2.4	4-8 / 1.2-2.4	4-8 / 1.2-2.4	4-8 / 1.2-2.4
Bracket	Wall	Wall	Wall	Wall
Ship Weight	13.75 lb. (6.3 kg)	27.75 lb. (12.6 kg)	37.75 lb. (17.1 kg)	49 lb. (22.2 kg)
Unit Height	17.375 in (44.1 cm)	19.75 in (50.2 cm)	26.375 in (67 cm)	26.875 in (68.2 cm)
Unit Width	8.25 in (21 cm)	12 in (30.5 cm)	12 in (30.5 cm)	13 in (33 cm)
Unit Diameter	5.25 in (13.3 cm)	6.89 in (17.5 cm)	6.89 in (17.5 cm)	8 in (20.3 cm)
Cylinder Material	Aluminum			