

TR-MONITOR-2

Addressable Dual Monitor Module

The TR-MONITOR-2 is an addressable monitor module with two initiating circuits for use with Triga fire alarm control panels (FACPs). The TR-MONITOR-2 acts as an interface to contact devices, such as waterflow switches and pull stations.

The TR-MONITOR-2 supports Class B supervised wiring to the load device. Conventional 4-wire smoke detectors can be monitored for alarm and trouble conditions.

Because the TR-MONITOR-2 is capable of monitoring two separate Class B circuits, it is ideal for waterflow tamper switch and flow switch monitoring.

INSTALLATION

The TR-MONITOR-2 mounts directly into a 4" square electrical box. The box must have a minimum depth of 2-1/8". A surface mount electrical box (TR-SMB500) is available from Triga.

COMPATIBILITY

The TR-MONITOR-2 is compatible with the following Triga Series FACPs:

- TR-2100R / TR-2100B
- TR-2100ECSR / TR-2100ECSB
- TR-R2100R / TR-R2100B



TR-MONITOR-2

FEATURES & BENEFITS

- Monitor two circuits, with unique addresses, simultaneously
- Support for Class B wiring
- Fully supervised
- Panel controlled status LED that flashes green in normal state and is solid red in alarm
- Rotary address switches for fast installation
- SEMS screws for easy wiring
- UL Listed
- FM Approved



Technical Specifications

PHYSICAL

Dimensions: 4.5" H x 4" W x 1.3 D (11.4 x 10.2 x 3.2cm)

Shipping Weight: 6.3oz (196g)

ELECTRICAL RATINGS

Operating Voltage: 15 - 32VDC

Maximum Current Draw: 6.4mA (LED on)

SLC Standby & Alarm Current: 750µA max @ 24

VDC (one communication every sec with 47k EOL)

End of Line Resistance: 47kΩ

ENVIRONMENTAL

Operating Temperature: 32°-120°F (0°C - 49°C)

Humidity: 10 to 93% non-condensing)

ORDERING INFORMATION

TR-MONITOR-2: Dual Monitoring Module

ACCESSORIES

TR-SMB500: 4" Square Surface Mount Electrical Box

This document is not intended to be used for installation purposes. We try to keep our product information up-to date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

TRIGA INVESTMENTS, LLC
340 Taxiway Bravo Beeville, TX 78102,
Tel: +1330-577-5199. Email: info@trigaglobal.com